



TRAXXAS SPRINT CAR

1. Chassis: Traxxas only. No aftermarket chassis. Rear motor only. Traxxas low-cg chassis may be used. **Original manufacturer chassis and suspension parts only (no RPM, no aluminum etc.).** Side "bumpers" may be removed. No alterations otherwise to chassis. Must use Traxxas Slash "stock" shocks and Traxxas Slash "stock" white springs only, (front on front, rear on rear) Shock internal limiters may be installed. No front bump stop suspension. A single original blue bump stop can be used per rear shock (not mandatory). Stock servo (2075) or the Savox servo (0252) are the only 2 servos that are to be used. After market front and rear bumpers permitted. Must be no wider than inside of tire.

2. Motor: Traxxas 12T Titan motor **only**. Labels on motor must be readable, No tape on labels or any signs of tampering with labels.

3. Battery: Battery must be 2 cell Lipo charged to 8.44V max up to 5200MAH/50C, Hard Case Only. NO HV Lipo. Labels on motor & battery must be readable, no tape, wires must be covered, No bare wires. No tape on batteries or no signs of tampering with labels

4. Tires/wheels: Traxxas Anaconda ONLY. Short course tires rear and rear 1/10 Buggy tire on the fronts.

5. ESC: Traxxas XL-5

6. Gearing: No gear rule

7. Body: McAllister Mercer Sprint Car Body – Driver optional. Front and top wing optional